

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number
WO 2005/028597 A1

(51) International Patent Classification⁷: **C10L 1/18**

(74) Agents: **MUNSON, Jeffrey, F.** et al.; The Lubrizol Corporation, 29400 Lakeland Blvd., Wickliffe, OH 44092 (US).

(21) International Application Number:
PCT/US2004/029979

(22) International Filing Date:
14 September 2004 (14.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/503,150 15 September 2003 (15.09.2003) US

(71) Applicant (for all designated States except US): **THE LUBRIZOL CORPORATION** [US/US]; 29400 Lakeland Boulevard, Wickliffe, OH 44092 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FORESTER, David R.** [US/US]; 3405 Foothills, Weatherford, Texas 76087 (US). **PRICE, David** [GB/GB]; 19 Ambervale Close, Littleover Derby DE23 7YB (GB). **BARBOUR, Robert H.** [GB/GB]; The Old Coach House, Hognaston, Ashbourne Derbyshire DE6 1PW (GB). **CERDA DE GROOTE, Carlos L.** [US/US]; 1446 Grace Avenue, Lakewood, OH 44107 (US). **SCHOBBER, Barton J.** [US/US]; 3208 Maine Avenue, Perry, OH 44081 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **LOW TEMPERATURE OPERABLE FATTY ACID ESTER FUEL COMPOSITION AND METHOD THEREOF**

(57) Abstract: A fuel composition comprises (A) a major amount of a fatty carboxylic acid ester composition from at least one naturally occurring triglyceride and (B) a minor amount of a low temperature operability composition. A method for improving the low temperature operability of a fuel composition comprises admixing (A) with a low temperature improving amount of (B). The fuel composition is derived from a renewable resource and is especially useful in internal combustion engines such as compression-ignited diesel engines.



WO 2005/028597 A1

Title: LOW TEMPERATURE OPERABLE FATTY ACID ESTER FUEL
COMPOSITION AND METHOD THEREOF

5

Background of the Invention

1. Field of the Invention

The present invention involves a fuel composition that comprises a fatty carboxylic acid ester from at least one naturally occurring triglyceride and a low temperature operability composition. The low temperature operability composition improves the low temperature operability of the fuel composition.

10

2. Description of the Related Art

Esterified fatty carboxylic acids, where the fatty carboxylic acids are derived from naturally occurring triglycerides, can be used as a partial or total replacement for a petroleum distillate and/or oxygenate in fuels for combustion in internal combustion engines and furnaces for locomotion, heating and power generation. The use of fatty carboxylic acid esters, which are derived from naturally occurring triglycerides, for combustion in fuels is particularly advantageous since naturally occurring triglycerides are renewable resources. Fuel compositions containing a major amount of a fatty carboxylic acid ester composition, about 30 wt.% or more of the ester composition, usually require a higher temperature for operability in terms of flow and filterability.

15

20

Erner in U.S. Patent No. 4,364,743 discloses a synthetic fuel of fatty acid esters that provides a novel source of energy when burned alone or in combination with other known fuels such as diesel oil, heating, etc. in oil-burning devices.

25

Tack et al. in U.S. Patent No. 4,863,486 disclose middle distillate fuel compositions with improved low temperature properties from polymers or copolymers having a narrow carbon number range of alkyl ester groups and containing a n-alkyl ester of a mono-ethylenically unsaturated C₄ to C₈ mono- or dicarboxylic acid wherein the average number of carbon atoms in the n-alkyl groups is from 12 to 14.

30

Dishong et al. in U.S. Patent No. 5,157,088 disclose low molecular weight terpolymers containing nitrogen and ester groups where the terpolymers are shear stable

and maintain desired high and low temperature viscosity characteristics in functional fluids such as automotive power transmission fluids.

Lal in European Patent Publication No. EP626442 discloses pour point treated fatty acid esters as biodegradable combustion engine fuels.

5 Corkwell et al. in U.S. Patent Application No. 10/640448, filed 13 August 2003, disclose a low temperature stable concentrate composition containing a fatty carboxylic acid based composition and a low temperature stability improving composition, and also discloses a fuel composition and method that employs the concentrate composition.

It has now been found that certain low temperature operability compositions are
10 extremely effective in improving the operability temperature of fuel compositions containing fatty carboxylic acid ester compositions derived from naturally occurring triglycerides by reducing the temperature required for operation in terms of flow and filterability, thus making these fuel compositions useful in the colder climates of Asia, Europe and North America.

15 Summary of the Invention

An object of the present invention is to provide a low temperature operable fuel composition containing a composition from a renewable resource for use in an internal combustion engine and/or furnace for locomotion, heating and power generation.

Another object of the present invention is to provide a low temperature operable
20 fuel composition containing a composition from a renewable resource for use in a spark-ignited and/or compression-ignited internal combustion engine.

Still a further object of this invention is a method to improve the low temperature operability of a fuel composition containing a composition from a renewable resource.

Additional objects and advantages of the present invention will be set forth in the
25 Detailed Description which follows and, in part, will be obvious from the Detailed Description or may be learned by the practice of the invention. The objects and advantages of the invention may be realized by means of the instrumentalities and combinations pointed out in the appended claims.

To achieve the foregoing objects in accordance with the present invention as
30 described and claimed herein, a fuel composition for an internal combustion engine comprises (A) a major amount of a fatty carboxylic acid ester composition from the transesterification of at least one naturally occurring triglyceride, and (B) a minor amount

of a low temperature operability composition comprising an esterified copolymer of an alpha-olefin or styrene and an alpha, beta-unsaturated monocarboxylic or dicarboxylic acid or anhydride, wherein the copolymer of (B) is esterified with a mixture of two or more alcohols having 5 to 28 carbon atoms wherein the mixture of the two or more alcohols has an average carbon length of 9.2 to 11.8 on a weight % basis.

In an embodiment of the invention the above described fuel composition comprises the fatty carboxylic acid ester composition of (A) and the low temperature operability composition of (B) comprising the esterified copolymer from two comonomers wherein the esterified copolymer further comprises an additional comonomer selected from the group consisting of a C_{1-4} alkyl alpha, beta-unsaturated monocarboxylic acid ester, a di(C_{1-4} alkyl) alpha, beta-unsaturated dicarboxylic acid ester, a vinyl monocarboxylic acid ester, an alkyl vinyl ether, and a mixture thereof.

In a further embodiment of this invention a method to improve the low temperature operability of the above-described fuel composition for an internal combustion engine comprises admixing the ester composition of (A) with a low temperature improving amount of the low temperature operability composition of (B).

Detailed Description of the Invention

A fuel composition of the present invention comprises (A) a major amount of a fatty carboxylic acid ester composition derived from at least one naturally occurring triglyceride, and (B) a minor amount of a low temperature operability composition comprising an esterified copolymer of an alpha-olefin or styrene and an alpha, beta-unsaturated monocarboxylic or dicarboxylic acid or anhydride, wherein the copolymer of (B) is esterified with a mixture of two or more alcohols having 5 to 28 carbon atoms wherein the mixture of the two or more alcohols has an average carbon length of 9.2 to 11.8 on a weight % basis.

The naturally occurring triglycerides of the present invention can be obtained from a renewable resource to include vegetable or plant fats and oils, animal fats and oils, and mixtures thereof. Vegetable or plant fats and oils include rapeseed oil, soybean oil, palm oil, corn oil, coconut oil, cottonseed oil, peanut oil, safflower oil, linseed oil, tung oil, castor oil, sunflower oil, meadowfoam oil, and mixtures thereof. In an embodiment of this invention the naturally occurring triglyceride is a rapeseed oil, a soybean oil, a

palm oil, or a mixture thereof. Animal fats and oils include lard, lard oil, tallow, various fish oils, and mixtures thereof.

The fatty carboxylic acid ester composition (A) of the present invention can be derived from at least one naturally occurring triglyceride, as described above, by transesterification of the triglyceride with an alcohol. In an embodiment of the invention the alcohol is at least one monohydric alcohol. The alcohol can be linear, branched, cyclic, or a mixture thereof. The alcohol can have 1 to 22 carbon atoms, and in other instances can have 1 to 18 carbon atoms, and 1 to 10 carbon atoms. Useful alcohols for transesterifying naturally occurring triglycerides include methanol, ethanol, propanol and butanol. The transesterification can be done using either an acid or base catalyst. Acid catalysts include dry hydrogen chloride and sulfuric acid. Base catalysts include alkali metal and alkaline earth metal alkoxides such as sodium methoxide, alkali metal hydroxides such as potassium hydroxide, and titanium alkoxides such as titanium tetraisopropoxide. The transesterification is generally run using an excess of the alcohol reactant and/or removing one of the products to drive the reaction toward completion. The fatty carboxylic acid esters from the transesterification of the triglyceride are usually isolated from the glycerol by-product and any excess alcohol reactant by physical separation and distillation or fractional distillation. In an embodiment of the invention rapeseed oil, soybean oil, palm oil, or a mixture thereof is transesterified with an excess of methyl alcohol using a sodium methoxide catalyst, as described in U.S. Patent No. 4,364,743 and European Patent Publication No. EP626442, to form fatty acid methyl esters which can be used in a fuel composition for an internal combustion engine to include a compression-ignited engine. In another embodiment of the invention fatty acid methyl esters are prepared by separate transesterifications of different triglycerides and then each fatty acid methyl ester can be used in a fuel composition as a single component or two or more of the fatty acid methyl esters can be used as a blend in a fuel composition. Fatty acid methyl esters such as rapeseed methyl ester, soy methyl ester and palm methyl ester are commercially available and are referred to as biodiesel fuels since they originate from naturally occurring triglycerides which are renewable resources.

The fatty carboxylic acid ester composition (A) of this invention can also be derived from at least one naturally occurring triglyceride, as described above, by esterification of one or more fatty carboxylic acids obtained from at least one naturally

occurring triglyceride. A fatty carboxylic acid or mixture of fatty carboxylic acids can be obtained from naturally occurring triglycerides by a saponification process and are commercially available. The fatty carboxylic acid or mixture of acids, obtained by saponification of at least one naturally occurring triglyceride, can be saturated, 5 unsaturated to include mono- and polyunsaturates, or a mixture thereof. The fatty carboxylic acid or mixture of acids can be linear, branched or a mixture thereof, but usually they are linear. The fatty carboxylic acid or mixture of acids can have 4 to 24 carbon atoms, and in other instances 8 to 22 carbon atoms, and 10 to 22 carbon atoms. The fatty carboxylic acid or mixture of acids can be esterified with an excess of an 10 alcohol, where the alcohol is as described above for the transesterification of a triglyceride, using an acid catalyst such as sulfuric acid and removing the water by-product by azeotropic distillation usually with an aromatic solvent. The sulfuric acid catalyst in the crude product can be neutralized, and the ester or esters can be recovered by fractional distillation as described in the esterification procedure in U.S. Patent No. 15 4,364,743. Alternatively, esterified fatty carboxylic acids or mixtures of esterified fatty carboxylic acids from naturally occurring triglycerides are commercially available. In an embodiment of the invention the fatty carboxylic acid or mixture of fatty carboxylic acids are esterified with an olefin such as ethylene.

The low temperature operability composition (B) of the present invention 20 comprises an esterified copolymer of an alpha-olefin or styrene and an alpha, beta-unsaturated monocarboxylic or dicarboxylic acid or anhydride. The alpha-olefin can have 2 to 30 carbon atoms, and in other instances can have 2 to 24 carbon atoms, and 2 to 20 carbon atoms. Useful alpha-olefins include ethylene, propylene, 1-butene, isobutylene, 1-hexene, 1-octene, 1-decene, 1-dodecene, 1-tetradecene, 1-hexadecene and 1-octadecene. 25 The alpha, beta-unsaturated monocarboxylic acid or anhydride can have 3 or more carbon atoms, and in other instances can have 3 to 6 carbon atoms, and 3 to 5 carbon atoms. Useful alpha, beta-unsaturated monocarboxylic acids include acrylic acid, methacrylic acid, crotonic acid and 2-pentenoic acid. The alpha, beta-unsaturated dicarboxylic acid or anhydride can have 4 or more carbon atoms, and in other instances can have 4 to 6 carbon 30 atoms, and 4 to 5 carbon atoms. Useful alpha, beta-unsaturated dicarboxylic acids and anhydrides include maleic acid, maleic anhydride, fumaric acid, itaconic acid and itaconic anhydride. In an embodiment of the invention the alpha, beta-unsaturated monocarboxylic

or dicarboxylic acid or anhydride is maleic acid, maleic anhydride, fumaric acid, itaconic acid, itaconic anhydride, acrylic acid, or methacrylic acid. In another embodiment of the invention the low temperature operability composition (B) comprises an esterified copolymer where the copolymer is formed from styrene and maleic anhydride. The copolymer of (B) can be prepared by a free radical polymerization of its two comonomers in a mole ratio of 0.25:1 to 1:0.25, and in other instances of 0.5:1 to 1:0.5, 0.75:1 to 1:0.75, and 1:1. The copolymer of (B) prior to esterification can have a reduced specific viscosity of 0.05 to 2, and in other embodiments can have a reduced specific viscosity of 0.05 to 1, and 0.07 to 0.8. The reduced specific viscosity of a polymer and its relation to the molecular weight of that polymer are defined and described in U.S. Patent No. 5,413,725 and in "Principles of Polymer Chemistry", Paul J. Flory, 1953 edition, page 308 and following pages. The copolymer of (B) is esterified with a mixture of two or more alcohols. The alcohols can be linear, branched, or a mixture thereof, but they are generally linear alcohols to include commercially available alcohols such as synthetic primary straight-chain alcohols made by Ziegler-type reaction of aluminum alkyls with ethane and hydrogen. The alcohols used to esterify the copolymer of (B) can have 5 to 28 carbon atoms, and in other embodiments can have 5 to 20 carbon atoms, 5 to 18 carbon atoms, and 5 to 16 carbon atoms. The copolymer of (B) can be esterified by the above described mixture of two or more alcohols to 50% or greater, and in other instances can be esterified to 65% or greater, 80% or greater, and 95% or greater. The copolymer of (B) can be esterified with a mixture of two or more alcohols or a copolymer of (B) can be esterified separately with each alcohol and the separately esterified copolymers combined, but usually the copolymer of (B) is esterified with a mixture of alcohols. In an embodiment of the present invention the copolymer of (B) is esterified with the above described mixture of two or more alcohols wherein the mixture of two or more alcohols has an average carbon length of 9.2 to 11.8 on a weight % basis, and in other embodiments has an average carbon length on a weight % basis of 9.8 to 11.7, 10.4 to 11.6, and 10.7 to 11.8. In another embodiment of the invention the esterification of the copolymer (B) with the above described mixture of two or more alcohols can be driven toward completion by including up to 20 mole %, based on carbonyl group equivalents, of lower molecular weight alcohols having 1 to 4 carbon atoms, and in other

embodiments up to 15 mole % and up to 10 mole % of the lower molecular weight alcohols can be included.

In an embodiment of the invention the esterified copolymer of (B) can have an unesterified portion remaining which can be reacted with up to 6 mole % of an amine, and in other instances up to 4 mole % and up to 2 mole % of the amine. The amine can be a monoamine or a polyamine, and usually the amine has only one amino group that is a primary or a secondary amino group. Examples of useful amines include ammonia, butylamine, diethylamine, N,N-dimethylethylenediamine, and aminoalkyl substituted heterocyclic compounds such as 4-(3-aminopropyl)morpholine.

In another embodiment of the invention the copolymer of (B), as described above, can further comprise an additional comonomer selected from the group consisting of a C₁₋₄ alkyl alpha, beta-unsaturated monocarboxylic acid ester, a di(C₁₋₄ alkyl) alpha, beta-unsaturated dicarboxylic acid ester, a vinyl monocarboxylic acid ester, an alkyl vinyl ether, and a mixture thereof. In still another embodiment of the invention the copolymer of (B) further comprises an additional comonomer which is methyl methacrylate. The additional comonomer is usually present in a minor amount relative to the other two comonomers that are used to form the copolymer of (B). The additional comonomer can be present at 0.3 mole or less per mole of either of the other two comonomers, and in other instances can be present at 0.2 mole or less and at 0.1 mole or less per mole of either of the other two comonomers. Examples of useful additional third comonomers include methyl methacrylate, methyl acrylate, diethyl fumarate, dimethyl maleate, vinyl acetate, vinyl propionate, and ethyl vinyl ether.

The above described esterified copolymer of (B) can be prepared by a free radical polymerization of the two or three comonomers to form a copolymer, an acid catalyzed esterification of the copolymer with a mixture of alcohols which optionally can include lower molecular weight C₁₋₄ alcohols to drive the esterification toward completion, usually neutralization of the esterification acid catalyst with a base such as an alkali metal hydroxide, and optionally reaction of remaining unesterified portions of the copolymer with an amine that has only one amino group that is a primary or a secondary amino group. During the esterification, azeotropic distillation with a solvent such as toluene is generally used to remove the water by-product and to drive the esterification toward completion. Prior to a final distillation and filtration of the crude esterified copolymer, an

oxidation inhibitor can be added at levels of 0.05 to 1% by weight of the final esterified copolymer product. The oxidation inhibitor can include hindered phenols and alkylated diarylamines. Also prior to the final distillation and filtration of the crude esterified copolymer, a diluent is typically added at a level of 5 to 50% by weight of the final
5 esterified copolymer product, and in other instances at a level of 10 to 40% by wt., and 15 to 30% by wt. The diluent can be a mineral oil, a solvent, or a mixture thereof. The solvent can be an aromatic hydrocarbon, an aliphatic hydrocarbon, an alcohol, or a mixture thereof. U.S. Patent No. 5,157,088 and European Patent Publication No. EP626442 provide a description of a general procedure for preparing esterified
10 copolymers from two or three comonomers of this invention.

The fatty carboxylic acid ester composition (A) can be present in the fuel composition of this invention from 1 to 99.99% by weight. The ester composition (A) is usually present in the fuel composition in a major amount from 10 to 99.99% by weight, and in other embodiments from 30 to 99.99% by weight, 55 to 99.99% by weight, and 80
15 to 99.99% by weight. The low temperature operability composition (B) can be present in the fuel composition in a minor amount from 100 to 10,000 ppm (parts per million) by weight, and in other embodiments from 500 to 9,000 ppm by wt., 1000 to 8000 ppm by wt., 1500 to 7000 ppm by wt., 2000 to 6000 ppm by wt., and 2000 to 5000 ppm by wt.

The above described fuel composition of the present invention can further
20 comprise (C) at least one additional fuel additive. The at least one additional fuel additive included in the fuel composition will generally depend on the application that the fuel composition is to be used for. A fuel composition intended for use in an internal combustion engine can further comprise at least one additional fuel additive to include nitrogen-containing detergents, amine-containing polyethers, metal-containing detergents,
25 antioxidants such as hindered phenols, rust inhibitors such as alkenylsuccinic acids, corrosion inhibitors such as alkylamines, combustion improvers such as nitroalkanes, demulsifiers, antifoaming agents, valve seat recession additives, metal deactivators, supplementary lubricity agents, bacteriostatic agents, gum inhibitors, anti-icing agents, anti-static agents, organometallic fuel-borne catalysts for improved combustion
30 performance, supplementary low temperature flow improvers, and fluidizers such as mineral oils, polyolefins and polyethers. The additional fuel additive or additives can be

present in the fuel composition depending on the function of each additive from 0.1 to 10,000 ppm by weight.

The fuel composition of this invention can further comprise (D) a normally liquid fuel. The normally liquid fuel can be a hydrocarbon fuel, a nonhydrocarbon fuel, or a mixture thereof. The hydrocarbon fuel can be a petroleum distillate to include a gasoline as defined by ASTM specification D4814 or a diesel fuel as defined by ASTM specification D975. The hydrocarbon fuel can be a hydrocarbon prepared by a gas to liquid process to include the Fischer-Tropsch Process, the Lurgi Process, the Oil/Gas Process, and the SASOL Process. The nonhydrocarbon fuel can be an oxygen-containing composition to include an alcohol, an ether, a nitroalkane, a plant or animal oil or fat, or a mixture thereof. The nonhydrocarbon fuel can be an oxygenated derivative of a hydrocarbon prepared by a gas to liquid process to include those listed above for hydrocarbon fuels such as the Fischer-Tropsch Process. Useful nonhydrocarbon fuels include methanol, ethanol, diethyl ether, methyl t-butyl ether, and nitromethane. Useful mixtures of fuels include a mixture of hydrocarbon fuels such as a mixture of a petroleum distillate and a gas to liquid process hydrocarbon, a mixture of nonhydrocarbon fuels such as a mixture of ethanol and methanol, and a mixture of hydrocarbon and nonhydrocarbon fuels such as a mixture of gasoline and ethanol and/or methanol, a mixture of a diesel fuel and ethanol, and a mixture of a gas to liquid process hydrocarbon and an alcohol and/or an ether and/or a nitroalkane. In an embodiment of the invention the normally liquid fuel is an emulsion of water in a hydrocarbon fuel, a nonhydrocarbon fuel, or a mixture thereof as described hereinabove. This emulsion can be prepared by a mechanical mixing, by including one or more emulsifiers and/or surfactants in the emulsion, or by a combination of mechanical mixing and inclusion of emulsifiers and/or surfactants. The normally liquid fuel can comprise a hydrocarbon fuel that has a reduced sulfur content such as a gasoline having a sulfur content at or below 1,000 ppm by wt. or a diesel fuel having a sulfur content at or below 500 ppm by wt. In an embodiment of the invention the normally liquid fuel (D) is a diesel fuel. The normally liquid fuel can be present in the fuel composition of the invention up to 98% by weight, and in other embodiments can be present in the fuel composition up to 69% by wt., up to 44% by wt., and up to 19% by wt.

The fuel composition of the present invention can be prepared by simply combining the above described components (A), (B), and optionally (C) and (D) at

ambient temperature. In another embodiment of the invention the fuel composition can be prepared by combining components (A), (B), and optionally (C) and (D), and mixing the combined components at an elevated temperature of 40 to 100°C until the composition is homogeneous.

5 A method of the present invention for improving the low temperature operability of a fuel composition, as described above, comprises admixing the above described ester composition (A) with a low temperature improving amount of the above described composition (B). The amount of the composition (B) to add can vary from 100 to 10,000 ppm by weight, and will normally increase as the amount of (A) increases in the fuel
10 composition. In an embodiment of the invention the amount of composition (B) to improve the low temperature operability of the fuel composition containing (A) is an amount of (B) that lowers the cold filter plugging point (CFPP), as measured by the ASTM D6371 standard test method for cold filter plugging point of diesel and heating fuels, of the fuel composition below the CFPP of an untreated sample of (A). In another
15 embodiment of the invention the amount of (B) to improve the low temperature operability of the fuel composition is an amount that lowers the CFPP of the fuel composition to -20°C or lower since most esterified fatty acids from plant and animal fats and oils, including transesterified naturally occurring triglycerides, have CFPP values well above -20°C.

20 The following examples are provided to demonstrate advantages of the present invention, but they are not intended to nor should they be used to limit the scope of the invention.

CFPP Evaluation of Biodiesel Fuel Compositions¹

Example	ACL ²	RME1 ³ °C(ppm)	RME2 ³ °C(ppm)	RME3 ³ °C(ppm)	RME4 ³ °C(ppm)
1 comparative	-	-14	-15.5	-13	-14
2 comparative	9.1	-14(6k)	-	-16(4k)	-
3	10.4	-13(6k)	-15(6k)	-24(3.5k)	-12(6k)
4	11.3	-20(2.5k)	-22(2.5k)	-21(2.5k)	-22(6k)
5 comparative	12.8	-18(4k)	-	-13.5(6k)	-

¹ The cold filter plugging points (CFPP) of biodiesel fuel compositions in examples 1-5 were measured per the ASTM D6371 standard test method. Example 1 provides CFPP values of four untreated rapeseed methyl ester samples as a comparative baseline. In examples 2-5 the CFPP values were measured for biodiesel fuel compositions containing the rapeseed methyl ester samples and varying levels of maleic anhydride-styrene copolymer esterified with alcohol mixtures that varied in average carbon length with examples 2 and 5 being comparative since their average carbon length is outside the present invention. Each of the esterified copolymers contained 20% by weight of an aromatic solvent.

² ACL is average carbon length of the alcohol mixture on a weight percent basis that was used to esterify the maleic anhydride-styrene copolymer.

³ RME1 through RME4 are the rapeseed methyl ester samples obtained from different suppliers and used in examples 1-5. The CFPP values are given in degrees centigrade and the values in parentheses are levels of esterified copolymers including aromatic solvent used to treat the rapeseed methyl esters in thousands of ppm by weight. For example, 6k represents a 6000 ppm by weight treatment level.

Each of the documents referred to in this Detailed Description of the Invention section is incorporated herein by reference. All chemical treatments or contents throughout this application regarding the present invention are understood to be as actives unless indicated otherwise even though solvents or diluents may be present.

What is claimed is:

- 5 1. A fuel composition for an internal combustion engine, comprising:
(A) a major amount of a fatty carboxylic acid ester composition from the transesterification of at least one naturally occurring triglyceride; and
(B) a minor amount of a low temperature operability composition comprising an esterified copolymer of an alpha-olefin or styrene and an alpha, beta-unsaturated
10 monocarboxylic or dicarboxylic acid or anhydride, wherein the copolymer of (B) is esterified with a mixture of two or more alcohols having 5 to 28 carbon atoms wherein the mixture of the two or more alcohols has an average carbon length of 9.2 to 11.8 on a weight % basis.
- 15 2. The fuel composition of claim 1 wherein the naturally occurring triglyceride is a vegetable oil.
3. The fuel composition of claim 2 wherein the vegetable oil is a rapeseed oil, a soybean oil, a palm oil, or a mixture thereof.
- 20 4. The fuel composition of claim 1 wherein the naturally occurring triglyceride is transesterified with at least one monohydric alcohol having 1 to 22 carbon atoms.
5. The fuel composition of claim 3 wherein the rapeseed oil, the soybean oil, the
25 palm oil, or the mixture thereof is transesterified with methanol.
6. The fuel composition of claim 1 wherein the alpha, beta-unsaturated monocarboxylic or dicarboxylic acid or anhydride is maleic acid, maleic anhydride, fumaric acid, itaconic acid, itaconic anhydride, acrylic acid, or methacrylic acid.
- 30 7. The fuel composition of claim 6 wherein the copolymer of (B) is formed from styrene and maleic anhydride.

8. The fuel composition of claim 7 wherein the copolymer of (B) prior to esterification has a reduced specific viscosity of 0.05 to 2.
- 5 9. The fuel composition of claim 1 wherein the copolymer of (B) further comprises an additional comonomer selected from the group consisting of a C₁₋₄ alkyl alpha, beta-unsaturated monocarboxylic acid ester, a di(C₁₋₄ alkyl) alpha, beta-unsaturated dicarboxylic acid ester, a vinyl monocarboxylic acid ester, an alkyl vinyl ether, and a mixture thereof.
- 10 10. The fuel composition of claim 9 wherein the additional comonomer is methyl methacrylate.
11. The fuel composition of claim 1 wherein the copolymer of (B) is esterified with a
15 mixture of two or more alcohols having 5 to 20 carbon atoms.
12. The fuel composition of claim 1 wherein the esterified copolymer of (B) is further reacted with an amine having only one amino group that is a primary or a secondary amino group.
- 20 13. The fuel composition of claim 1 wherein the ester composition (A) is present in the fuel composition from 30 to 99.99% by weight and the low temperature operability composition (B) is present in the fuel composition from 100 to 10,000 ppm by weight.
- 25 14. The fuel composition of claim 1, further comprising:
(C) at least one additional fuel additive.
15. The fuel composition of claim 1, further comprising:
(D) a normally liquid fuel.
- 30 16. The fuel composition of claim 15 wherein the normally liquid fuel is a diesel fuel.

17. A method for improving the low temperature operability of a fuel composition, comprising:

admixing the ester composition (A) with a low temperature improving amount of the composition (B) of claim 1.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US2004/029979

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C10L1/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 626 442 A (LUBRIZOL CORP) 30 November 1994 (1994-11-30) cited in the application	1-17
Y	page 4, line 10 - line 36 page 7, line 1 - page 8, line 54 page 9, line 18 - line 24 page 15, line 4 - line 15 page 27, line 26 - line 49; claims 1,2,4-7,14	1-17
X	WO 94/10267 A (DAVIES BRIAN WILLIAM ; LOMBARDI ALLESSANDRO (GB); LEWTAS KENNETH (US);) 11 May 1994 (1994-05-11) page 4, line 21 - line 27 page 10, line 18 - page 12, line 17; claims 1-4	1-7, 11-16

-/--

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

19 November 2004

Date of mailing of the international search report

29/11/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Deurinck, P

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US2004/029979

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 772 706 A (WEERS JERRY J ET AL) 30 June 1998 (1998-06-30) column 3, line 58 - column 4, line 57 -----	1-17
A	EP 0 807 676 A (ETHYL PETROLEUM ADDITIVES LTD) 19 November 1997 (1997-11-19) page 4, line 26 - page 5, line 20; claims 1,4 -----	1-17
A	US 5 441 545 A (TACK ROBERT D ET AL) 15 August 1995 (1995-08-15) claim 1 -----	1-17

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US2004/029979

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0626442	A	30-11-1994	AU 674052 B2	05-12-1996
			AU 5901694 A	01-12-1994
			CA 2117278 A1	25-11-1994
			DE 69419456 D1	19-08-1999
			DE 69419456 T2	05-01-2000
			EP 0626442 A1	30-11-1994
			ES 2135542 T3	01-11-1999
WO 9410267	A	11-05-1994	AT 140474 T	15-08-1996
			AU 674179 B2	12-12-1996
			AU 5336094 A	24-05-1994
			BR 9307307 A	01-06-1999
			CA 2146542 A1	11-05-1994
			DE 69303722 D1	22-08-1996
			DE 69303722 T2	28-11-1996
			WO 9410267 A1	11-05-1994
			EP 0665873 A1	09-08-1995
			FI 951965 A	25-04-1995
			JP 8502539 T	19-03-1996
			NO 951552 A	24-04-1995
			RU 2129587 C1	27-04-1999
			US 5743923 A	28-04-1998
			ZA 9307916 A	01-06-1994
US 5772706	A	30-06-1998	AU 8303398 A	25-03-1999
			EP 0903396 A1	24-03-1999
			US 5857287 A	12-01-1999
EP 0807676	A	19-11-1997	US 6086645 A	11-07-2000
			CA 2204806 A1	17-11-1997
			DE 69723912 D1	11-09-2003
			DE 69723912 T2	15-07-2004
			EP 0807676 A2	19-11-1997
			JP 10053777 A	24-02-1998
			KR 228992 B1	01-11-1999
			SG 74585 A1	22-08-2000
			TW 418249 B	11-01-2001
US 5441545	A	15-08-1995	AT 80413 T	15-09-1992
			CA 1331511 C	23-08-1994
			CN 86106777 A ,B	27-05-1987
			DE 3686687 D1	15-10-1992
			DE 3686687 T2	25-03-1993
			EP 0214786 A1	18-03-1987
			JP 1980692 C	17-10-1995
			JP 7010983 B	08-02-1995
			JP 62096591 A	06-05-1987